

ALUMINIUM MADE EASY
YOUR COMPLETE ALUMINIUM
WINDOW & DOOR RANGE.




REAL ALUMINIUM. THE FINER CHOICE.



REAL
ALUMINIUM

WHY REAL ALUMINIUM? IT'S AS EASY AS CHILD'S PLAY...



- ✓ Easy Pricing
- ✓ Easy Quoting
- ✓ Easy Choices
- ✓ Quick Delivery
- ✓ Quick Quoting

REAL Aluminium fabricates a comprehensive range of aluminium fenestration products for all domestic and commercial installations. Manufactured using profiles and components held in stock at the dedicated factory in Gloucestershire.

All stock
aluminium
products on a
2-week
turnaround

With strong, slim profiles and long-lasting quality materials and finish, REAL Aluminium covers a full suite of aluminium products. That includes: casement windows, bi-folding doors, sliding doors, residential doors and composite doors.

LEAD TIMES

Quoting – 24 hours or
immediate via pricing tools

Delivery – 2 weeks*

*From sign off/next delivery date

Astragal bar products = 3 weeks

Grey exterior and white interior = 2 weeks

Composite door bespoke colours = 3 weeks

COLOUR OPTIONS

White, Black, Grey,
Grey Exterior/White Interior

OUR PROFILES

The REAL Aluminium range of products provide a full solution for any aluminium installation with a choice of contemporary or traditional styles.

Window, residential door and French door options include 'Square', our standard profile-style window or 'Featured', a more traditional profile replicating the ovolo style of a traditional timber window.

MARKETING SUPPORT

Our Marketing Team are happy to support you and are on hand to help.

Contact us on: 01642 309574 or
email enquiries@thetradevillage.co.uk

A SERVICE YOU CAN RELY ON

Each and every product within the REAL Aluminium range is manufactured from stocked profile and components. Should there be any requirements for replacements or remakes these can be turned around in 1 week, compared to 3 weeks or more for non-stocked products.





ALUMINIUM...THE FINER CHOICE

Why choose aluminium?

There are a multitude of reasons to choose aluminium. Homeowners are becoming more aware of the benefits of this slimmer and stronger material for their home. Improvements to aesthetics and thermal performance differentiate today's aluminium products from those of the eighties and nineties.

Aluminium is the preferred product of discerning architects...why would discerning homeowners choose anything else? Whatever the taste or style of your home, the REAL Aluminium range offers distinctive styles and designs to suit.

Aluminium – designed and built to last.

Slimmer profile

The slimmer and stronger aluminium frames increase the ratio of glass to frame therefore letting more light into your home. Clean joints and subtle lines offer a luxurious finish for homeowners to admire.



Typical PVCu



REAL Aluminium

Up to 50%
slimmer
than PVCu

LONG-LASTING COLOUR

Powder-coated aluminium is one of the most durable finishes available for windows and doors. It won't discolour, rust or peel, giving it a long-lasting, attractive appearance.

All aluminium products from the REAL Aluminium range come with superior guarantees. This guarantee covers the powder-coating against the following faults:

- peeling, powdering and blistering
- corrosion
- chalking, fading and loss of sheen

Refer to the Care & Maintenance Instructions for guarantee exclusions: www.real-aluminium.co.uk



HIGH STRENGTH

Aluminium, by its very nature, is a strong material compared to PVCu and doesn't require additional reinforcements.

The superior strength of aluminium allows for larger arrangements which are only possible with timber or PVCu when using bulky profiles and couplers.

Most PVCu bi-folds can only extend to 750mm-wide sashes; the REAL Aluminium Bi-folding Doors can accommodate 1200mm sashes.

EASE OF MAINTENANCE

Aluminium is easy to keep looking great and is virtually maintenance free. Modern powder-coating delivers a hard-wearing finish which will last for years.

With occasional cleaning and periodic lubrication of locks and hinges, aluminium windows and doors will look and operate 'as-new' for longer.



Refer to the Care & Maintenance Instructions for details: www.real-aluminium.co.uk

BETTER FUNCTIONALITY

Aluminium is a durable substance, therefore windows and doors made from aluminium will continue to open and slide smoothly over many years.

ENVIRONMENTALLY FRIENDLY

Aluminium is infinitely recyclable, and when recycled uses just 5% of the total energy needed to produce frames from scratch.

THERMALLY EFFICIENT

The REAL Aluminium range is enhanced with polyamide thermal barrier technology, enabling the windows and doors to exceed the energy performance requirements of current Building Regulations.

Profiles used in all products from the REAL Aluminium range have a very high resistance to heat transfer from the inner face of the frame to the external face of the frame, giving superior thermal efficiency and reduced condensation.



YOUR COMPLETE ALUMINIUM WINDOWS & DOORS

Suitable for all property types from traditional cottages to contemporary town houses.



Building Regulation compliance, Window Energy Ratings (WER) and Doorset Energy Ratings (DSER)



Compliance with current Building Regulations is a vital part of every installation and can sometimes be complex. Using REAL Aluminium, meeting the requirements of Part L of current UK Building Regulations, is easy as the entire range is compliant using energy ratings for renovations to existing properties when installed with a double-glazed unit with a U Value of 1.2 w/m²k and a solar gain of 0.71 or better

that is manufactured using an Edgetech Super Spacer Bar or equivalent. All REAL Casement Windows achieve an 'A'-rating if the aforementioned glass unit is upgraded to low-iron glass. The thermal efficiency of the REAL Aluminium range can be enhanced further by using higher-performance double-glazed or triple-glazed units.

REAL Aluminium WER, DSER & U Values

WER: Window Energy Performance Certificate WER Window Energy Rating - In accordance with Approved Document L

A

B

C

D

E

F

G

A

Company

Customade/REAL

Project

REAL Alitherm 400
I Window

Date

14 Jul 2022

BFRC System

SC010

BFRC Manufacturer

M117
M117

BFRC Simplified Energy Licence

SEL

WER:	Window Energy Rating: 196.74((1-f)xgglass) - 68.5 x (U + (0.0165 xAL))	3.2 kWh/m ² /Year
Thermal Transmittance:	WER U Value of window calculated using the methods and conventions set out in BR443 Whole window U Value with frame, glazing and glass spacer bar combined. Standard window configuration set out by BR443/GGF 2.3 U Window: 0.496+0.919+0.143	1.6 W/m ² K
Frame:	Supplier: Smart Architectural Aluminium System: Alitherm 400 KB Outer Frame: ETC4110F (1.556) Vent Frame: ETC4129F (2.218) Transom Mullion: ETC4130F (2.112) Heat Transfer: 2.024 W/m ² K x (24.5% Frame)	0.496 W/m ² K
Glazing:	Supplier: Glass Systems Specification: 4/20/4 Clear Softcoat Low Iron 1.2 CPV Centre Pane, g Value: 1.217 W/m ² K, 0.74 Heat Transfer: 1.217 W/m ² K x (75.5% Glass)	0.919 W/m ² K
Spacer:	Supplier: Edgetech Spacer Bar: Super Spacer Premium Heat Transfer: 0.035 W/m ² K x (4.092m ²)	0.143 W/m ² K
U Value:	Window U Value: Calculation to BR443/GGF 2.3	1.6 W/m ² K

BFRC

Calculated in accordance with UK Building Regulations Document L and BR443
BS EN ISO 10077-2: Thermal performance of windows, doors and shutters.
Calculation of thermal transmittance. Part 2: Numerical method for frames

Version 6.0 (0327)

U Value: Certificate Window U Value - In accordance with Approved Document L

U Value

1.2 W/m²K

Company

Customade/REAL

Project

REAL System 1 -
Triple glazed window

Date

14 Jul 2022

BFRC System

SC010

BFRC Manufacturer

M117
M117

BFRC Simplified Energy Licence

SEL3310

WER:	Window Energy Rating: 196.74((1-f)xgglass) - 68.5 x (U + (0.0165 xAL))	-18.4 kWh/m ² /Year
Thermal Transmittance:	WER U Value of window calculated using the methods and conventions set out in BR443 Whole window U Value with frame, glazing and glass spacer bar combined. Standard window configuration set out by BR443/GGF 2.3 U Window: 0.566+0.531+0.125	1.2 W/m ² K
Frame:	Supplier: Smart Architectural Aluminium System: Alitherm 300 Outer Frame: *ZSB169FF (1.915) Vent Frame: ETC424N (2.947) Transom Mullion: ETC333 (3.104) Heat Transfer: 2.699 W/m ² K x (21.0% Frame)	0.566 W/m ² K
Glazing:	Supplier: Glass Systems Specification: 4/12/4/12/4 clear/softcoat 1/softcoat 1 0.7 CPV Centre Pane, g Value: 0.672 W/m ² K, 0.42 Heat Transfer: 0.672 W/m ² K x (79.0% Glass)	0.531 W/m ² K
Spacer:	Supplier: Edgetech Spacer Bar: Super Spacer Premium Heat Transfer: 0.030 W/m ² K x (4.165m ²)	0.125 W/m ² K
U Value:	Window U Value: Calculation to BR443/GGF 2.3	1.2 W/m ² K

BFRC

Calculated in accordance with UK Building Regulations Document L and BR443
BS EN ISO 10077-2: Thermal performance of windows, doors and shutters.
Calculation of thermal transmittance. Part 2: Numerical method for frames

Version 6.0 (0323)









Note:
All REAL Aluminium products when used in conjunction with the glass specifications on pages 8,9,10 and 11 satisfy current Building Regulations Part L for refurbishment and new-build applications.

The addition of low-iron glass will not improve U Values but will improve WER/DSER rating due to solar gain.

The addition of triple glazing will improve U Values but due to reduced solar gain has limited effect on WER/DSER ratings.







REPLACEMENT ON EXISTING DWELLINGS OR EXTENSIONS (Energy ratings)

REQUIREMENT	WINDOW / DOOR DESIGN	SYSTEM	DOUBLE GLAZED UNIT SPEC	ACTUAL RATING	
B rated or U_w 1.4 W/m ² k		Alitherm 300 Window System 1 (F)	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	B	Band A achievable with low iron glass + FF insulation
		Alitherm 300 Window System 2 & 5 (F)	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	B	
		NEW PRODUCT Alitherm 400 Window (F)	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	A*	
>60% glazed door C rated or U_d 1.4 W/m ² k		NEW PRODUCT Alitherm 400 Resi Door (F)	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	C	
C rated or U_d 1.4 W/m ² k		NEW PRODUCT Alitherm 400 French Door (F)	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	C	Band B achievable with low iron glass
C rated or U_d 1.4 W/m ² k		Visofold 1000 SLIM Bi-fold door	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	C	Band B achievable with low iron glass
C rated or U_d 1.4 W/m ² k		Visoglide Plus Sliding Door	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	C	Band B achievable with low iron glass + F insulation
B rated or U_w 1.4 W/m ² k		Ecofutural TBT	28mm unit clear/argon/softcoat 1.2 Centre pane 1.22 W/m ² k warm edge spacer	B	

Glass type 1.2 -examples K glass S, Planitherm Total, Climaguard A+

*Internally glazed Alitherm 400 windows need low iron glass to achieve an A rating.

EXTENSIONS U VALUES (Limiting U value 1.4 W/m²k)

REQUIREMENT	WINDOW / DOOR DESIGN	SYSTEM	GLAZED UNIT SPEC	ACTUAL UW/UD
B rated or Uw 1.4W/m ² k		Alitherm 300 Window System 1 (F)	Triple glazed 36mm unit clear/softcoat 1.2/softcoat 1.2 Centre pane 0.8 W/m ² k warm edge spacer	1.3 W/m ² K
		Alitherm 300 Window System 2 & 5 (F)	Triple glazed 36mm unit clear/softcoat 1.2/softcoat 1.2 Centre pane 0.8 W/m ² k warm edge spacer	1.3 W/m ² K
		NEW PRODUCT Alitherm 400 Window (F)	Double glazed 28mm unit clear/argon/softcoat 1 Centre pane 1.068 W/m ² k warm edge spacer	1.4 W/m ² K
>60% glazed door C rated or Ud 1.4W/m ² k		NEW PRODUCT Alitherm 400 Resi Door (F)	Double glazed 28mm unit clear/argon/softcoat 1 Centre pane 1.068W/m ² k warm edge spacer	1.4 W/m ² K
C rated or Ud 1.4W/m ² k		NEW PRODUCT Alitherm 400 French Door (F)	Double glazed 28mm unit clear/argon/softcoat 1 Centre pane 1.07W/m ² k warm edge spacer	1.4 W/m ² K
C rated or Ud 1.4W/m ² k		Visofold 1000 SLIM Bi-fold door	Triple glazed 44mm unit clear/softcoat 1.2/softcoat 1.2 Centre pane 0.7 W/m ² k warm edge spacer	1.3 W/m ² K
C rated or Ud 1.4W/m ² k		Visoglide Plus Sliding Door (F)	Triple glazed 36mm unit clear/softcoat 1.2/softcoat 1.2 Centre pane 0.76 W/m ² k warm edge spacer	1.3 W/m ² K
B rated or Uw 1.4W/m ² k		Ecofutural TBT	Double glazed 28mm unit clear/argon/softcoat 1 Centre pane 1.068W/m ² k warm edge spacer	1.4 W/m ² K







Glass type 1.2 -examples K glass S, Planitherm Total, Climaguard A+, Glass type 1 -examples Pilkington S1, Planitherm one, Climaguard 1

NEW BUILD U VALUES WITH DOUBLE GLAZING (Limiting U value 1.6 W/m²k)

REQUIREMENT	WINDOW / DOOR DESIGN	SYSTEM	DOUBLE GLAZED UNIT SPEC	ACTUAL UW/UD
Uw 1.6 W/m²k minimum Uw 1.2 W/m²k Target		Alitherm 300 Window System 1 (FF)	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.6 W/m²K
		Alitherm 300 Window System 2 & 5 (FF)	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.5 W/m²K
		NEW PRODUCT Alitherm 400 Window (F)	28mm unit clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.4 W/m²K
>60% glazed door Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		NEW PRODUCT Alitherm 400 Resi Door (F)	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.4 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		NEW PRODUCT Alitherm 400 French Door (F)	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.4 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		Visofold 1000 SLIM Bi-fold door	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.6 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		Visoglide Plus Sliding Door (F)	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.6 W/m²K
Uw 1.6 W/m²k minimum Uw 1.2 W/m²k Target		Ecofutural TBT	28mm clear/argon/softcoat 1 Centre pane 1.068 W/m²k warm edge spacer	1.4 W/m²K

Glass type 1 -examples Pilkington S1, Planitherm One, Climaguard 1

NEW BUILD U VALUES WITH TRIPLE GLAZING NOTIONAL METHOD (Target U value 1.2 W/m²k)

REQUIREMENT	WINDOW / DOOR DESIGN	SYSTEM	TRIPLE GLAZED UNIT SPEC	ACTUAL UW/UD
Uw 1.6 W/m²k minimum Uw 1.2 W/m²k Target		Alitherm 300 Window System 1 (FF)	36mm unit clear/softcoat 1/softcoat 1 Centre pane 0.7 W/m²k warm edge spacer	1.2 W/m²K
		Alitherm 300 Window System 2 & 5 (FF)	36mm unit clear/softcoat 1/softcoat 1 Centre pane 0.7 W/m²k warm edge spacer	1.2 W/m²K
		NEW PRODUCT Alitherm 400 Window (F)	40mm unit clear/softcoat 1/softcoat 1 Centre pane 0.63 W/m²k warm edge spacer	1.1 W/m²K
>60% glazed door Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		NEW PRODUCT Alitherm 400 Resi Door (F)	40mm unit clear/softcoat 1/softcoat 1 Centre pane 0.63 W/m²k warm edge spacer	1.1 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		NEW PRODUCT Alitherm 400 French Door (F)	40mm unit clear/softcoat 1/softcoat 1 Centre pane 0.63 W/m²k warm edge spacer	1.1 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		Visofold 1000 SLIM Bi-fold door NEW BEAD	44mm unit clear/softcoat 1/softcoat 1 Centre pane 0.6 W/m²k warm edge spacer	1.2 W/m²K
Ud 1.6 W/m²k minimum Ud 1.2 W/m²k Target		Visoglide Plus Sliding Door (F)	36mm unit clear/softcoat 1/softcoat 1 Centre pane 0.72 W/m²k warm edge spacer	1.3 W/m²K
Uw 1.6 W/m²k minimum Uw 1.2 W/m²k Target		Ecofutural TBT	36mm unit clear/softcoat 1/softcoat 1 Centre pane 0.67 W/m²k warm edge spacer	1.1 W/m²K

Glass type 1 -examples Pilkington S1, Planitherm One, Climaguard 1

+Note: Triple glazing reduces light transmission to the inside



AD L: ENERGY EFFICIENCY - NEW DWELLINGS

The Notional dwelling Target 'U' Values for Windows and Doors are laid out in Table 1.1 of the Approved Document L.

The notional method enables Architects to trade off 'U' values against other materials in the dwelling as long as they are within the limiting 'U' values.

Table 1.1 from Doc L

DESCRIPTION	TARGET 'U' VALUE
Windows	1.2 W/m ² K
Doors with glazed area greater than 60%	1.2 W/m ² K
Other doors	1.0 W/m ² K

The lowest specification 'U' Value allowable referred to as the Limiting 'U' Values are shown in Table 4.1.

Table 4.1 from Doc L

DESCRIPTION	LIMITING 'U' VALUE
Windows	1.6 W/m ² K
Doors	1.6 W/m ² K



AD L: ENERGY EFFICIENCY - EXISTING DWELLINGS

3.2 'U' Values, Window Energy Ratings (WER) and doorset energy ratings (DSER) of replacement windows and doors must be both:

- No worse than that of the element being replaced
- Meet the limiting standards in Table 4.2 (Lowest specification of 'U' Value or WER/DSER allowable)

Table 4.2 from Doc L

DESCRIPTION	'U' VALUE	WER/DSER
Windows	1.4 W/m ² K	B
Doors with glazed area greater than 60%	1.4 W/m ² K	C
Other doors	1.4 W/m ² K	B

'U' Values, Any windows and doors replaced will need to be at least the level of performance detailed in Table 4.2 above.

FRESHER, CLEANER INDOOR AIR (PART F)

The new Simon TTF Slimline is a through-frame trickle ventilator that is a robust, yet attractive aluminium ventilator. With its built-in updraught and various operating modes the TTF Slimline is a stylish and effective product that perfectly complements our beautiful REAL profiles.



SIMON TTF SLIMLINE

- Independently tested to BS EN 13141-1:2019
- Water tightness of 400pa
- Independently acoustically tested in accordance with BS EN 20140-10:1992, ISO 140-10:1991.
- Tested in accordance with BS EN 1026:2016 & BS EN 1027: 2016 Weather performance

AD F: VENTILATION - NEW DWELLINGS

Table 1.7 from Doc F

ROOM TYPE	MINIMUM EQUIVALENT AREA OF BACKGROUND VENTILATORS FOR DWELLINGS WITH MULTIPLE FLOORS	MINIMUM EQUIVALENT AREA OF BACKGROUND VENTILATORS FOR SINGLE STORY DWELLINGS
Habitable Room (see note 2 & 3)	8,000mm ²	10,000mm ²
Kitchen (see note 2 & 3)	8,000mm ²	10,000mm ²
Utility Room	NO MINIMUM	NO MINIMUM
Bathroom (see note 4)	4,000mm ²	4,000mm ²
Sanitary Accommodation	NO MINIMUM	NO MINIMUM

The use of this table is not appropriate in the following situations or conditions and expert advice must be sought.

- 1a) If the dwelling has only one exposed facade (e.g. within a multi-storey building).

1b) If the dwelling has 70% of its openings on the same facade.

1c) If a kitchen has no windows or external facade where a ventilator could be installed.

2) Where a kitchen and living room accommodation are not separate rooms (i.e. open plan), no fewer than three ventilators of the same equivalent area as for other habitable rooms should be provided within the open plan space (8,000mm²).
- 3) The total number of ventilators installed in the dwelling's habitable rooms and kitchen/s should be no fewer than five, except in one bedroom properties where there should be no fewer than four.

4) If a bathroom has no window or external facade through which a ventilator can be installed, the minimum equivalent area specified should be added to the ventilator sizes specified in nearest adjoining rooms. (i.e. 8,000mm² increased to 12,000mm² and 10,000mm² increased to 14,000mm²).

AD F: VENTILATION - REPLACEMENT WINDOWS

If the existing windows have background ventilators, the replacement windows should have background ventilators that are:-

- i) No smaller than the background ventilators in the original windows.
- ii) Be controllable either automatically or by the occupant.

If the existing windows do not have background ventilators and there is no mechanical ventilation with a heat recovery system, it is necessary to ensure that the ventilation provision in the dwelling is no worse than it was before the work was carried out.

This may be demonstrated in any of the following ways:-

- i) Incorporating background ventilators in the replacement windows equivalent to column one in the above table 1.7.
- ii) If there is a continuous mechanical extract ventilation, replacement windows in habitable rooms which are not wet rooms must have a minimum background ventilation area of 4,000mm².
- iii) Other ventilation provisions, if it can be demonstrated to a building control body that they comply.

Note: If it is not technically feasible to adopt the minimum equivalent areas set out in the above table 1.7, the background ventilators should have equivalent areas as close to the minimum value as is feasible.



ELEGANT, SLIM SIGHTLINE
- Up to 50% slimmer than PVCu




CASEMENT WINDOWS

The REAL Casement Windows range offers ultimate flexibility with numerous combinations of top-hung sashes, side-hung sashes, dummy sashes and fixed lights available that are ideal for residential installations.

All REAL Aluminium profiles utilise innovative polyamide thermal break technology which creates a barrier between the cold air outside and the warm air inside. This technology significantly reduces thermal transmittance and enhances the overall U Value of a product, allowing REAL Aluminium casement windows to achieve a Window Energy 'A' Rating when used in conjunction with the correct double-glazed unit. .

Choose from two styles available within the REAL Aluminium range: Square, our standard style window or Featured, a more traditional profile replicating the ovolo style of a traditional timber window. Both options are available internally or externally glazed.

For a truly classic look, why not add Georgian or Astragal bars?



REAL SYSTEM 1 & 2

SQUARE – CONTEMPORARY


EXCLUSIVE TO REAL ALUMINIUM

The square-edged profile of the 'Contemporary' window provides clean, slim sightlines and a modern finish to any home.

System	Modified 70mm Alitherm 300
Finish	Polyester powder coated
WER	up to A-rating using suitable double-glazed unit
U Value	up to 1.2 w/m²k using suitable triple-glazed unit
Locking system	Espag locking
Frame depth	70mm
Typical sightline	67mm
SH Max o/a width	600mm
SH Max o/a height	1400mm
TH Max o/a width	1400mm
TH Max o/a height	1400mm
Glazing	28mm double-glazed or 36mm triple-glazed



Available colours:



REAL SYSTEM 5 **N.B Discontinued for 2023**

FEATURED – CLASSIC-AL

EXCLUSIVE TO REAL ALUMINIUM

The elegant sculptured featured profile of a Classic-al window closely resembles the traditional look of timber windows with slimmer sightlines giving an increased glass area, bringing more light into the home.

System options	Modified 70mm Alitherm 300
Finish	Polyester powder coated
WER	up to A-rating using suitable double-glazed unit
U Value	up to 1.2 w/m²k using suitable triple-glazed unit
Locking system	Espag locking
Frame depth	70mm
Typical sight line	67mm
SH Max o/a width	600mm
SH Max o/a height	1400mm
TH Max o/a width	1400mm
TH Max o/a height	1400mm
Glazing	28mm double-glazed or 36mm triple-glazed



Available colours:



White



Full range of couplers, bay poles and add-ons available from stock

System options

- 1 Contemporary frame – flat sash, internally glazed, square bead with dummy sashes
- 2 Contemporary frame – bevel sash, externally glazed, square bead
- 5 Classic-al frame – featured sash, externally glazed, bevel bead

ALITHERM 400 RANGE



The new Alitherm 400 offers outstanding quality, performance and value via a range of stylish casement windows and single and double doors. As the first thermally broken aluminum system to feature an extruded glazing gasket, it provides enhanced performance and reduced installation time.

Its innovative design incorporates polyamide thermal break technology that significantly reduces thermal transmittance, enhancing the systems overall 'U' value. Available in neutral colours, Alitherm 400's new Quick-Glaze Bead is simply tapped in on site with the gasket already in place, eliminating the need for wedge gaskets on internally beaded windows. Making for a faster, simpler and more cost-effective glazing process.

Features and specifications:

- Fully compliant with changes to document L of the building regulations
- Improved thermal and weather performance
- Brand new quick glaze bead for a simpler, faster and cost-effective glazing process.
- PAS 24: 2016 approved for added security
- Unlimited colour choice provided by any RAL colour on top of the stock colour selections

Alitherm 400 Windows

Alitherm 400 windows are currently available in two options. The popular Alitherm 400 I range is an internally beaded system with dummy sashes which can achieve PAS 24 security standards. Alternatively, we have the externally glazed Alitherm 400 X range, which can be upgraded to PAS 24 security standards with the introduction of glass security clips.

Quick-Glaze tap in bead standard on internally glazed windows with 28mm double glazing.



SPECIFICATION ALITHERM 400 WINDOW

System	Alitherm 400*
Finish	Polyester powder organic coating to BS6496
WER	down to A+ rating using suitable double glazed unit
U Value	down to 1.1 w/m ² k with triple-glazing
Handles	Espag locking handles by ERA
Frame depth	70mm
Typical sight line	71.5mm
SH Max o/a width	850mm
SH Max o/a height	1400mm
TH Max o/a width	1400mm
TH Max o/a height	1500mm
Glazing	28mm double glazed or 40mm triple glazed

*Externally glazed and triple glazed windows require wedge gasketing.



RESIDENTIAL OR FRENCH DOORS

Our elegant, yet strong and durable aluminium residential or French doors enhance the beauty of a home, keep in the warmth and let in more light due to their slim sightlines.



Open out or open in, the REAL Aluminium Residential or French Door is a high-performance product suitable for use in high traffic or exposed areas where a durable and reliable door is required. Available as single or double doors, both with internal beading. Adjustable hinges, colour-matched flat panels and a double seal make the REAL Aluminium Residential Doors a perfect option for any home.

Alitherm 400 Doors

Suitable for both residential and commercial applications, Alitherm 400 doors perfectly complement the window range, offering the same stylish lines and same ease of fabrication and installation. With unrivalled thermal performance and security assurance, the system is available as open-in or open-out, single or double doors.

Quick-Glaze tap in bead standard on internally glazed doors with 28mm double glazing.



SPECIFICATION ALITHERM 400 DOOR

Peace of mind is ensured with the inclusion of an enhanced security multi-point locking system on double doors. Security can be further enhanced with additional shootbolts.

All main sections feature an extended Polyamide thermal break that allows the residential doors from the REAL range to achieve a U Value of 1.4 W/m²K when installed with a suitable double-glazed sealed unit.




System	Alitherm 400
U Value	up to 1.1 w/m ² k using a suitable triple-glazed unit
Security	Multi-point locking & 3 star cylinder
Max height	2400mm
Max width	1100mm
Max weight	100kg
Glazing	28mm double-glazed or 40mm triple-glazed

*Triple glazed doors require wedge gasketing.

Available colours:

Square Profile:



Aluminium designer door panels are available.

SLIDING DOORS

A REAL Aluminium Sliding Door adds eye-catching impact to the exterior of a home. The outward appearance focuses on stunning glass areas, highlighted by bold aluminium sections styled with clean aesthetic lines that work in harmony with the character of any home.



Delivering optimum performance and tested to the highest standards REAL Aluminium Sliding Doors guarantee reliability. The strong and thermally broken aluminium sections make large sliding doors and large glass areas possible without compromising thermal performance or weather resistance.

Special sliding mechanisms enable even the largest sashes to slide effortlessly, whatever the size. Each sliding panel can be up to 2500mm high and when closed these large sliding doors form a thermally efficient glass facade, a wonderful way to flood a space with light and to enjoy beautiful views.


This adaptable system is ideal for use as residential sliding doors that maximise light and give stunning unimpeded views or as sliding commercial entrances where large opening apertures are required.

REAL Aluminium Sliding Door profiles have been designed to improve both strength and weather resistance. All main sections feature an extended Polyamide thermal break that allows the sliding doors from the REAL range to achieve a U Value of 1.6 W/m²K when installed with a standard double-glazed sealed unit.

SPECIFICATION




Configuration examples:



System	Visoglide Plus
Finish	Polyester powder coated
U Value	up to 1.3 w/m²k using a suitable triple-glazed unit
Security	Multi-point locking plus individual keeps
Frame depth	99mm or 126mm double track 165.5mm or 182.5mm triple track
Max sash weight	200kg
Max sash height	2500mm
Max sash width	Within above limitations
Glazing	28mm double-glazed or 36mm triple-glazed
Track	Double or triple dependent on configuration

Available colours:



HANDLES AND ACCESSORIES

Use the reference chart below to discover the perfect set of handles and accessories for your home.

							
			White	Black	Grey	Graphite	Chrome
BI-FOLDING DOORS	Lever (straight) handle		✓	✓	✓	✓	✓
	Intermediate handle		✓	✓	✓		✓
	D handle		✓	✓	✓		✓
	Magnetic catch		✓	✓	✓		✓
	Trickle vents		✓	✓	✓		
SLIDING PATIO DOORS	Long lever handle		✓	✓	✓		
	Sliding Door D handle		✓	✓	✓		
CASEMENT WINDOWS	Offset handle		✓	✓	✓	✓	✓
	Monkey tail handle						
ENTRANCE & FRENCH DOORS	Lever (straight) handle		✓	✓	✓	✓	✓
	Lever (swan) handle						
	Letterplate (black ABS surround)		✓	✓			✓
	Letterplate (matching surround)		✓	✓		✓	✓
COMPOSITE DOORS	Lever (straight) handle		✓	✓	✓	✓	✓
	Pull Knob		✓	✓		✓	✓
	D Bar						
	Inline Round Pull Bar						
	Inline Flat Pull Bar						
	Centre Escutcheon						
	Pull Escutcheon		✓	✓		✓	✓
	Letterplate (matching surround)		✓	✓		✓	✓
	Knocker 6" Urn		✓	✓		✓	✓
	Knocker 6" Urn with spyhole		✓	✓		✓	✓
	Knocker 8" Urn Slimline		✓	✓		✓	✓
	Bull Ring Knocker		✓	✓		✓	✓
	Numerals 0-9						✓

A range of locking cylinders are available to give enhanced security on bifold and sliding doors. **Please speak to your REAL retailer for details.**



Satin Silver

Polished Gold

Stainless Steel

Antique Black

✓	✓		
✓			
✓*			
✓			
✓	✓		
			✓
✓	✓		
			✓
✓	✓		
✓	✓		✓
	✓	✓	✓
	✓	✓	✓
		✓	
		✓	
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	
	✓		✓
			✓
	✓		

LOCKS

REAL Aluminium doors that have more than one lock will only require one key to operate all of them (this is called 'keyed alike'). Separate doors will have unique keys unless specified. Alitherm 400 doors have a high-security key system (3 Star System) as standard. With our standard high-security key system (3 Star System), all keys will be unique. For further details, please speak to your REAL Retailer.



Antique black range



Composite door only

*silver anodised SAA



MAKE QUOTING AND ORDERING ALUMINIUM AS EASY AS CHILD'S PLAY...

Aluminium can be a little tricky to cost and has a reputation for being on a longer lead time. The REAL Aluminium range makes aluminium easy to understand, easy to price, easy to quote and provides a sensible choice of windows and doors.

MAKING ALUMINIUM EASY TO UNDERSTAND

- ✓ Easy Pricing
 - ✓ Easy Quoting
 - ✓ Easy Choices
 - ✓ Quick Delivery
 - ✓ Quick Quoting
-

REAL
ALUMINIUM